

# LEGACY<sup>®</sup>

*High Profile Laminate  
SBS Class 4 Impact Shingles*



Shown in:  
Natural Wood

 **Malarkey**  
**Roofing Products**<sup>™</sup>  
Defining Excellence.<sup>™</sup>

[WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM)



ANTIQUÉ BROWN



BLACK OAK



HEATHER



MIDNIGHT BLACK




NATURAL WOOD



OXFORD GREY



RAINFORREST



SIENNA BLEND



SILVERWOOD



STORM GREY



WEATHERED WOOD

# LEGACY® & LEGACY®



## SCOTCHGARD™ PROTECTION FROM 3M

Regions that are prone to algae growth should inquire about our Legacy® shingles featuring the Scotchgard™ protection from 3M. The Legacy® shingles featuring the 20 year Scotchgard™ Algae Resistant Roofing System warranty from 3M are equipped with the most effective solution available against algae staining.

## EXTREME WEATHER PROTECTION

The Legacy® provides a durable barrier against extreme weather, receiving the UL 2218 Class 4 Impact Resistance classification, the highest rating possible.

In a Class 4 rating test, the Legacy® withstood a simulation of hailstones impacting a roof at 90 mph (144 kph) without sustaining damage.

## RUGGED DURABILITY

Malarkey's revolutionary Legacy® shingle technology begins with a durable base layer of fiberglass mat. Malarkey's unique fiberglass mat is coated on both sides with the SBS modified rubber asphalt which provides tensile strength and increased flexibility, protecting your investment.

Additional weight in the shingle is providing long term weatherability and granule adhesion; protecting your investment.

## SBS MODIFIED ASPHALT

The rubberizing aspect of SBS increases flexibility and weatherability for your roof. The thermo cycling resilience of SBS modified asphalt provides greater granule adhesion for the shingle to create a better barrier from the elements. When granules stay on the shingles, your roof lasts longer.

## ZONE®

One of the most critical aspects of a successful roofing project is correct shingle installation. Improper fastener placement is the leading cause of incorrect shingle installation and can subsequently void the warranty. The Legacy® is manufactured using the patented ZONE® technology which includes a tapered nailing area over three times larger than other laminate shingles. The ZONE's® larger nailing area dramatically improves correct fastener placement.

## RAIN SEAL PROTECTION

Malarkey's Legacy® shingle is manufactured with a double line of defense in the critical area for a laminated shingle, with double SEBS asphalt rain seal protection.

The SEBS asphalt has elongation capabilities of up to 800 percent, making it flexible down to zero degrees. The rain seal remains intact through the freeze and thaw cycle. Malarkey SEBS asphalt adhesive is superior to oxidized asphalt because of its cohesive and adhesive properties. The adhesive properties of SEBS asphalt join the shingle together while the cohesive properties prevent it from breaking apart from itself.

## LIMITED WIND WARRANTY

Legacy® shingles come with a 110 mph/177 kph Limited Wind Warranty.

## ENHANCED WIND WARRANTY

Legacy® shingles are eligible for a 130 mph/209 kph Enhanced Wind Warranty Protection when Malarkey's Smart Start™ shingle is installed, shingles are six nailed, and Malarkey's supporting products-Artic Seal 401, Right Start UDL, or Malarkey Hip and Ridge Shingle (EZ-Ridge™ 222-224\*) or Hip & Ridge Strips (225\*-227\*)\*\* are used.

## TEST COMPLIANCE

- ASTM D7158 Class H
- ASTM D3161 Class F
- ASTM E108 Class A
- CSA A123.5
- FBC Approval - #14809
- ASTM D3462
- ASTM D3018 Type I
- UL 2218 Class 4
- ICC Approval - ESR 3150



## FEATURING

- 50 Year Limited Material Warranty
- 10 year Right Start™ Warranty
- Your Choice™ Warranty Program

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Limited warranties carry terms and conditions. Contact your nearest Malarkey source for further information. See Malarkey Your Choice™ Warranty for details.

\*Malarkey Roofing systems require algae resistant EZ-Ridge XT™ 224 shingles or Hip and Ridge shingles 225 & 227, in conjunction with the algae resistant shingles, to receive the full 20 year algae resistant warranty system. The Alaskan® (230) featuring Scotchgard™ Algae Resistant Protection from 3M can be substituted as Hip and Ridge shingle, in conjunction with the algae resistant shingles to receive the full 20 year algae resistant warranty system. 3M and Scotchgard are trademarks of 3M Company.

\*\* Some contractors adapt roofing shingles for use as a hip and ridge shingle. If your contractor uses this method, the Enhanced Wind Warranty will apply when The Alaskan® (230) is used as hip and ridge shingles. Use of Dura-Seal shingles for hip and ridge will not qualify toward Enhanced Wind Warranty.

† Internal specification allows for variance of ± 4% in weight. This version supersedes all previous versions. Rev. 11/12



Defining Excellence.™

P.O. BOX 17217, Portland, OR 97217

503.283.1191 | 800.545.1191 | Fax: 503.289.7644

WWW.MALARKEYROOFING.COM